

ALI-143 Battery



Lithium-lon

Features:

Ш	High	per	formance	rec	hargea	able	Lithium	i-ion	batter	у.
---	------	-----	----------	-----	--------	------	---------	-------	--------	----

- ☐ Durable high impact plastic housing and connector enclosure.
- ☐ High capacity and reliability well sealed construction Lithium-ion battery.
- $\hfill \square$ Electrical safety protection circuit included
- ☐ Each Unit cell contains safety air -vented.
- ☐ Protection against short circuit and improper charge.
- ☐ Unit contains safety vented cells
- ☐ 100% final testing

Items

PT Model no

Average Voltage

Nominal Capacity

Dimensions

Operating Temp

Storage Temp

Exterior/Housing

Connector

State of Charge Indicator

Replacement for

APPLICATIONS

Specification

PTO-ALI-143

Nominal 14.4V, Maximum voltage: 16.8V

17.5Ah

225*80*85mm

-20°C to +60°C

-20°C to +50°C

Hard Plastic Case

2 Hole Socket and Aux Side Connector

5 Segment LCD with Constant Display

ALI-143

Manpack Transceiver PR4G



Global Produits Energétiques

www.gpe.com.tn

hajem.moncef@gpe.com.tn

26 AV de l'UMA Tunis Carthage ARIANA TUNISIE Tel: +216 71 940 200

Tel: +216 71 940 200 Fax: +216 71 940 964