



# BA-386/PRC-25 Battery

- High performance non-rechargeable Alkaline battery.
- Durable high impact plastic housing and connector enclosure
- High reliability due to all welded construction
- Unit contains safety vented cells



This battery meets the requirements of B-49030 for:

- Battery voltage
- Capacity test
- Electrolyte leakage
- Mechanical and thermal shock
- Vibration
- Insulation resistance

Alkaline Manganese Dioxide

For use in	PRC-77 and PRC-25 radio sets
Replacement for	BA-3386/PRC-25, BA-4386/PRC-25, BA-5598/U, BA-386/PRC-25
Cell chemistry	Alkaline Manganese Dioxide
Nominal voltage A2	15.0 Volts
Nominal voltage A1	3.0 Volts
Typical capacity	A2: 15.0Ah, A1: 4.9Ah
Nominal dimensions	240 x 92 x 54mm
Nominal weight	1.87kg
Connector	Floating type
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Shelf life	5 years



**Global Produits Energétiques**  
 Site web: [www.gpe.com.tn](http://www.gpe.com.tn)  
 Mail: [hajem.moncef@gpe.com.tn](mailto:hajem.moncef@gpe.com.tn)  
 Adresse : Tunis Carthage  
 ARIANA TUNISIE  
 Tel: +216 71 940 200  
 Fax: +216 71 940 964  
 Mobile : +216 29 047 852