



BA-4386/PRC-25 Battery

- High performance non-rechargeable
- Durable high impact plastic housing and connector enclosure.
- High reliability due to all welded construction.
- Unit contains safety vented cells.



This battery is engineered and designed for use in a world wide tactical environment, and is manufactured to meet and exceed ISO9000 methods and procedures.

The BA 49030 (Alkaline) with reference to STD-810 for:

Battery voltage	Capacity test	Electrolyte leakage
Mechanical and thermal shock	Vibration	Insulation resistance

For use in	AN/PRC-77 and AN/PRC-25 radio sets
Replacement for	BA-3386/PRC-25, BA-4386/PRC-25, BA-5598/U, BA386/PRC
Cell chemistry	Alkaline Manganese Dioxide
Nominal voltage A2	15.0 Volts
Nominal voltage A1	3.0Volts
Typical capacity	A2: 15.0Ah, A1: 4.9Ah
Nominal dimensions	240 x 92 x 54mm
Nominal weight	1.87kg
Connector	Floating type, 3 pins fitted
Case material	Modified ABS
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +55°C
Shelf life	5 years

Alkaline Manganese Dioxide



Global Produits Energétiques
 Site web: www.gpe.com.tn
 Mail: hajem.moncef@gpe.com.tn
 Adresse : Tunis Carthage
 ARIANA TUNISIE
 Tel: +216 71 940 200
 Fax: +216 71 940 964
 Mobile : +216 29 047 852