



BB-2590/U Battery

- High performance rechargeable Lithium-ion battery with instantaneous start up.
- Dual state of charge "gas gauge" LCD displays.
- Durable high impact plastic housing and connector enclosure
- High capacity, performance verified, hermetically sealed, lithium-ion cells.
- Protection against short circuit and improper charge



Lithium ion

For use in	PRC-104, PRC-119 (Singars), PRC-138, KY-57
Replacement for	BB-590/U, BB-390A/U, BB-390/U, BB-490/U, BA-3590/U, BA-5290/U and BA-5590/U
Cell chemistry	Rechargeable, lithium ion Battery
Nominal voltage	30 Volts or two 15V sections depending on connection
Typical Voltage	7.2Ah at 30.0V, 14.4Ah at 15.0V
Max Discharge	12.0A in 15.0V mode, 6.0A in 30.0V mode
Max Pulse Discharge	36.0Ah in 15.0V mode, 18.0Ah in 30.0V mode
Nominal dimensions	112 x 63 x 127 mm
Normal weight	1.36kg
Connector	Equivalent to SC-C-179495
Case material	Modified ABS, drab olive green
Operating temperature	-40°C to +65°C
Shelf Life	Five years under controlled storage.



Global Produits Energétiques
Site web: www.gpe.com.tn
Mail: hajem.moncef@gpe.com.tn
Adresse : Tunis Carthage
ARIANA TUNISIE
Tel: +216 71 940 200
Fax: +216 71 940 964
Mobile : +216 29 047 852