

# BB-516A/U Battery

- High performance rechargeable Nickel Cadmuim battery.
- Battery with state of charge display.
- This battery is used for various military communications and electronics applications.
- This battery must be conditioned to prior to use to obtain maximum capacity.



**Nickel Cadmuim Battery**

For use in	AN/GVS-5 (Melios)
Replacement for	BB-516/U , BB-326/U
Recommended Chargers	PP-8498/U , PP-8333/U , PP-8481B/U
Cell chemistry	Nickel Cadmuim
Nominal voltage	24.0 Volts
Capacity	0,250 Ah
Nominal dimensions	36 x 36 x 91mm
Weight	0.27kg
Connector Environmental	2 Pure Nickel Contacts
Operating temperature	-20°C to +55°C
Storage temperature	-40°C to +40°C



**GPE**  
Global Produits Energétiques

**Global Produits Energétiques**  
 Site web: [www.gpe.com.tn](http://www.gpe.com.tn)  
 Mail: [hajem.moncef@gpe.com.tn](mailto:hajem.moncef@gpe.com.tn)  
 Adresse : Tunis Carthage  
**ARIANA TUNISIE**

Tel: +216 71 940 200  
 Fax: +216 71 940 964  
 Mobile : +216 29 047 852