

Charger

BTC-70819

Portable Battery Charger (SPC Lite)



When Ordering Specify P/N:

BTC-70819



Description:

The BTC-70819 is a state of the art portable battery charger designed for field or depot use. Charger is capable of charging 2 batteries simultaneously in 3 hours or less with easy to follow LED lighting sequences. Charger will charge and maintain the range of military communication and electronic batteries using designated adapter.

Charging system is upgradeable in the field or a lab environment through the RS232 port.

Charger has been CE Qualified.

Technical Data	
National Stock Number	6130-01-555-7817
BTPartNo.	BTC-70819
Dimensions	Length: 14.5in(369.0mm)Width: 11.0in(280.0mm)Height: 8.0in(204.0mm)
Weight(Nominal)	13.0lbs (5.9Kg)
Power Requirements	90 to 264 VAC (47 to 420 Hz) or 22-33 VDC
Case Material and Color	High Impact Plastic Resin
Operating Temperature Range	-20°Cto +50°C(-4°F to +122°F)
Storage Temperature	-40°Cto +70°C(-40°F to 158°F)
PowerCables	60" (1.52m) ACCable, Optional DC Cables Available
Packaging	Unit box 1 per; Weight: 18.51b (8.4 Kg); Cubes: 0.7ft³ (.02m³)

26 Avenue de l'UMA, Tunis Carthage 2035 - ARIANA, TUNISIA Tel +216 71 940 200 Fax +216 71 940 964 Email : hajem.moncef@gpe.com.tn Web site : www.gpe.com.tn