

<i>Description</i>	Rechargeable, Lithium-Ion, (Carbon/Lithiated Metal Oxide) Battery with "State of Charge Display".
<i>Nato Stock Number</i>	6140-14-328-2258
<i>For Use In</i>	Handheld Radio Set PR4G, RCU, TDT and COMLOC.
<i>Replacement for</i>	ALI -124
<i>Nominal Dimensions</i>	Length: 2.625 in (67 mm) Width: 0.905 in (23 mm) Height: 3.463 in (88 mm)
<i>Nominal Weight</i>	1.06 Lb (482 g)
<i>Nominal Voltage</i>	7.2 V
<i>Cutoff Voltage</i>	5.0 V
<i>Nominal Capacity</i>	7.2 AHr @ 1A
<i>Operating Temperature Range</i>	-20°C to +55°C (-4°F to +131°F)
<i>Storage Temperature Range</i>	-40°C to +55°C (-40°F to +131°F)
<i>Shelf Life</i>	Up to 5 Yr dependent on storage conditions.
<i>Case Material & Color</i>	Aluminum case, NATO - iR SC/C 24X5 (sand color optional)
<i>Connector</i>	2 Hole socket .
<i>Charging</i>	Recommended Charger is the "ALT-170".
<i>Standard Charge</i>	Charge at constant voltage 8.4V for 5 1/2h.
<i>Disposal</i>	Environmentally Safe - Contains Zero (0)% Mercury or Cadmium. Check with local regulations for proper disposal.
<i>Packaging</i>	Unit Box 1 per, Master Carton 72 per Weight: 82 lb (37.19Kg); Cubes .51ft ³ (.014m ³)

WHEN ORDERING SPECIFY P/N:
BT-70483

