

BTC-70480S

ALI Solar Charger



Description

Used with Lithium-Ion batteries for the ALI 143, ALI 243, ALI 147, and ALI 247. The ALI 143 and ALI 243 will charge in 7 hours typically, while the ALI 147 and ALI 247 will charge in 4.5 hours typically.

BTC-70480S is equipped with a two-pin "trailer-hitch" connector, and can be powered from a solar panel*, power supply*, 24V vehicular power, or almost any DC power source between 10V and 36V. (* sold separately)

This charger is a simple, flexible, and portable solution for the user who does not require a bulk or multi-station charger.

When Ordering Specify PN:
BTC-70480S

Technical Data

National Stock Number	Pending
BT Part No.	BTC-70480S
Dimensions	Length: 2.71in (68.83mm) Width: 1.93in (49.02mm) Height: 1.75in (44.45mm)
Weight	0.31Lbs (0.14Kg)
Power Requirements	10- 36VDC, 57WMax
Case Material	Modified ABS Plastic, Black
Operating Temperature Range	-20°C to +50°C (-4°F to +122°F)

26 Avenue de l'UMA, Tunis Carthage 2035 - ARIANA, TUNISIA Tel +216 71 940 200
 Fax +216 71 940 964 Email : hajem.moncef@gpe.com.tn
 web site: www.gpe.com.tn