



Bren-Tronics, Inc.
"Military Batteries & Charging Systems"

CHARGERS

BTC -70822 -MR

Medium Rate Battery Cap Charger



Description: BTC-70822-MR is a dedicated single-station charger that will charge the:

- BB-2590/U in six hours or less
- BB-2557/U in three hours or less
- BB-390B/U in eleven hours or less

BTC-70822-MR can be powered from 115/230 Vac, 50/60 Hz mains power, or from 12Vdc automotive power sources.

This charger is a simple solution for the user who does not require a bulk or multi-station charger.

When Ordering Specify P/N:
BTC-70822-MR

Technical Data

National Stock Number	Pending
BT Part No.	BTC-70822-MR
Dimensions, Nominal	<p>Charger: Length 3.27" (83mm), Width 2.15" (55mm), Height 1.98" (50mm)</p> <p>Power Supply: Length 5.40" (137mm), Width 2.12" (54mm), Height 1.08" (28mm)</p> <p>Cable Lengths: AC input 36" (0.9m), DC input 36" (0.9m), Supply-to-Charger 53" (1.3m)</p> <p>Charger security strap: Length 13.5" (0.34m) with ends in secure position.</p>
Weight(Nominal)	1.50lb (0.68kg)
Operating Temperature	-20°C to +50°C (-4°F to 121°F)
Storage Temperature	-40°C to +70°C (-40°F to 158°F)
Color	Black (all components and cables)
Packaging	Includes storage pouch for power supply and AC/DC input cables.

26 Avenue de l'UMA, Tunis Carthage 2035 - ARIANA, TUNISIA Tel +216 71 940 200
Fax +216 71 940 964 Email : hajem.moncef@gpe.com.tn
www.gpe.com.tn